

## FLW4006 Powerful model in tower version

The FL models shown here have higher cooling capacity, powerful circulating pumps, and internal bath volumes of up to 30 liters. 2 variants: Air-cooled (FL) and water-cooled (FLW).

### Your advantages

- Ergonomic design and easy operation
- Splash-proof keypad
- Large, bright LED display
- Reliable Microprocessor PID temperature control
- Precise PID temperature control
- Powerful immersion pumps, suitable for continuous operation
- Permissible temperature in return line +80°C
- Easy filling from the top with hinged protective lid
- Low liquid level protection with optical and audible alarm signal
- Integrated stainless steel bath tanks
- Removable ventilation grid
- Front drain
- No side vents, instruments can be placed right next to other equipment
- RS232 interface for PC connection
- IP class according to IEC 60529: 21
- Alarm output, potential-free change-over contact (max. 30 VA)
- Pressure Indicator
- By-pass valve to adjust pump pressure



### Technical data

Available voltage versions		Bath	
Order No.	9 676 040	Bath tank	Stainless steel
Available voltage versions:			
9 676 040.16	230V/3PPE/60Hz (Without Plug)		
9 676 040.07	400V/3PNPE/50Hz (Plug 16A CEE)		
Cooling		Other	
Cooling of compressor	1-stage Water	Sound pressure level dbA	65
Cooling water pressure max. bar	87	Classification	Classification I (NFL)
Cooling water difference pressure psi	29 ... 87	IP Code	IP 21
1.0Cooling water consumption l/min	6.6	Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Temperature control	PID1	Weight lbs	352.7
Temperature displayTemperature display	LED	Cooling Water Connection in	G $\frac{3}{4}$
Temperature settingTemperature setting	Keypad	Barbed fittings inner diameter	1"
		Dimensions in. (W x L x H)	23.6 x 29.9 x 45.3
		Filling volume l	24 ... 30
		Pump connections	G1 $\frac{1}{4}$ " male
Temperature values			
Setting the resolution of the temperature display °C	0.1		
Return flow temperature max. °C	80		
Working temperature range °C	-15 ... +40		
Temperature stability °C	±0.5		

Ambient temperature °C	5 ... 40
Temperature display resolution °C	0.1

## Performance values

### 230V/3PPE/60Hz (Without Plug)

#### 230V/3PPE/60Hz

Cooling capacity (Water Glycol)

°C	20	10	0	-10
kW	4	3	1.7	0.7

Refrigerant	R449A
Filling volume g	850
Global Warming Potential for R449A	1397
Carbon dioxide equivalent t	1.187
Pump capacity flow rate l/min	60
Pump capacity flow pressure psi	7.3 ... 87

### 400V/3PNPE/50Hz (Plug 16A CEE)

#### 400V/3PNPE/50Hz

Cooling capacity (Water Glycol)

°C	20	10	0	-10
kW	4	3	1.7	0.7

Refrigerant	R452A
Filling volume g	1100
Global Warming Potential for R452A	2140
Carbon dioxide equivalent t	2.354
Pump capacity flow rate l/min	60
Pump capacity flow pressure psi	7.3 ... 87

## All Benefits



**Precise**  
PID Temperature control with set control parameters, temperature stability  $\pm 0.02 \dots \pm 0.2$  °C



**JULABO. Quality.**  
Highest standards of quality for a long product life.



**Green technology.**  
Development consistently applied environmentally friendly materials and technologies.



**Satisfied customers.**  
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



**100% Checked.**  
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



**Quick start.**  
Individual JULABO consultation and comprehensive manuals at your disposal.



**Services 24/7.**  
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at [www.julabo.com](http://www.julabo.com).