

## PRESTO A70 Process system

The air-cooled PRESTO A70 is JULABO's most compact 2-stage process system and offers high cooling capacities for lowest temperatures down to -75 °C.


The highly dynamic temperature control systems PRESTO are designed for high-precision temperature control for a wide range of applications such as reactor vessels or material stress tests. Moreover, by using efficient components, the process systems can compensate exothermic and endothermic reactions exceptionally fast. Permanent internal monitoring and self-lubricating pumps ensure a long life-time. In addition, numerous interfaces offer many remote control possibilities across networks or for integration into higher-level control systems.



### Product features


- Analog connections, RS485, Profibus DP (accessory)
- Space optimized design creates more room directly next to the units
- External Pt100 sensor connection
- Built-in 5.7" industrial color touchscreen
- Second external Pt100 sensor connection (accessory)
- Alarm output
- Temperature stability  $\pm 0.01$  °C ...  $\pm 0.05$  °C
- Pump pressure up to 1.7 bar, max. flow rate 40 l/min
- Removable ventilation grid

### Heat-up time




Medium: Thermal HL90

### Cool-down time



Medium: Thermal HL90

### Pump Capacity



### Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)	
Heating capacity kW	1.8
Viscosity max. cSt	50
Pump capacity flow pressure l/min	0 ... 40
Pump capacity pressure psi	1.5 ... 24.7
Power consumption A	16

Order No. 9420701.N1.03

**Cooling capacity 1 (Ethanol)**

°C	20	0	-20	-40	-50	-60	-70
kW <sup>1</sup>	1.12	1.1	0.98	0.9	0.69	0.45	0.23

**Cooling capacity 2 (Ethanol)**

°C	20	0	-20	-40	-50	-60	-70
kW <sup>1</sup>	1	0.91	0.8	0.75	0.55	0.38	0.12

**Cooling capacity 4 (Thermal HL90)**

°C	20	0	-20	-30	-40	-50	-60	-70
kW <sup>1</sup>	0.96	0.87	0.8	0.76	0.72	0.61	0.35	0.12

**Note about natural refrigerants:**

Temperature control units using natural refrigerants are often subject to regulatory requirements regarding the installation site, operation, transport or disposal of the units. If you have any questions, we will be happy to advise you.

Refrigerant stage 1		Refrigerant stage 2	
Refrigerant	R449A	Refrigerant	R170
Filling weight g	650	Filling weight g	99
Global Warming Potential for R449A	1397	Global Warming Potential for R170	6
Carbon dioxide equivalent t	0.90805	Carbon dioxide equivalent t	0.000594

<sup>1</sup> Performance specifications measured in accordance with DIN 12876. Cooling capacities up to 20 °C measured with ethanol; over 20 °C with thermal oil unless otherwise specified. Performance specifications apply at an ambient temperature of 20 °C. Performance values may differ with other bath fluids. Cooling capacity 1 = capacity at minimum pump level, cooling capacity 2 = capacity at maximum pump level

**Technical data**

**Available voltage versions**

Order No.	9 420 701
Available voltage versions:	
9420701.N1.14	208V/60Hz (Nema N6-20 Plug) (R449A)
9420701.N1.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F) (R449A)

**Other**

Sound pressure level dbA	63
Classification	Classification III (FL)
IP Code	IP 20
Pump type	Centrifugal Pump
Pump type Magnetically coupled	1

**Cooling**

Cooling of compressor	2-stage Air
-----------------------	-------------

**Electronics**

Interfaces	Alarm output, Ethernet, Modbus, Profibus optional, REG/EPROG optional, RS232, RS485 optional, SD memory card, Standby-Input optional, USB
External pt100 sensor connection	integrated
2nd external Pt100 sensor connection	accessory
Integrated programmer	8x60 steps
Temperature control	ICC
Absolute temperature calibration	3 Point Calibration
Temperature display	5.7" TFT Touchscreen
Temperature setting	Touchscreen

**Dimensions and volumes**

**Temperature values**

Internal usable expansion volume l	4.8	Setting the resolution of the temperature display °C	0.01
Minimal process volume l	2.3	Working temperature range °C	-75 ... +250
Active heat exchanger volume l	1.7	Temperature stability °C	±0.01 ... ±0.05
Weight lbs	308.6	Ambient temperature °C	+5 ... +40
Dimensions in. (W × L × H)	22.4 × 25.2 × 34.6	Temperature display resolution °C	0.01
Pump connections	M24x1.5 male		

## All Benefits



### Touch display. Perfect operation.

With the touch display, the user always has an overview of all values and functions. The intuitive and multilingual menu structure enables perfect control.



### Convenience for several users

Administrator level for customizing instrument settings, user levels with limited permissions for fast and safe defined access, password protection, all levels adjustable



### 100 % Cooling capacity

'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



### Intelligent temperature control.

Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.



### Full control

'Temperature Control Features', for individual optimization, access to all important control parameters, additional settings for band limit, limits, co-speedfactor etc.



### Control of the external application

External Pt100 sensor connection for precise measurement and control directly in the external application



### Highest measuring accuracy

'Absolute Temperature Calibration' for manual compensation of a temperature difference, 3-point calibration



### Intelligent pump system

Reliable and consistent pump capacity, electronically adjustable pump stages or pressure value, automatic adjustment of pump capacity to viscosity



### Many interfaces.

Straight-forward remote control, data management, and integration into process structures. USB, Ethernet, RS232, SD card, and alarm off are permanently integrated. Further interfaces available as accessories.



### Space-saving footprint

All connections as well supply and exhaust air are located at the front or rear, no venting grids on the sides, units can be placed close to each other or the application



### Continuous operation up to +40 °C

Robust temperature control instrument, continuous operation even at ambient temperatures of up to +40 °C



### Maximum safety.

Classification III according to DIN12876-1 enables safe operation, even with flammable fluids. Automatic switch-off in the event of high temperature or low liquid level.



### Duplicate safety

Adjustable high temperature cut-off for internal tank and for integrated expansion vessel




### For flammable bath fluid

Classification III (FL) according to DIN 12876-1



### Quick support

If an error occurs, the integrated Black-Box function permits fast diagnosis by the JULABO service team



### 100% Checked.

100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



**Quick start.**

Individual JULABO consultation and comprehensive manuals at your disposal.



**Services 24/7.**

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at [www.julabo.com](http://www.julabo.com).



**Satisfied customers.**

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.

